



Memrecam GX-5

The most experienced name in high-speed video introduces the GX-5, the expandable digital high speed camera with the versatility to handle a variety of applications!



NAC's **Memrecam GX-5** is setting new standards for high-speed imaging flexibility and performance in a variety of applications including: Vehicle Impact Testing, Onboard Airbag Deployment Testing, Safety Restraints Testing, Automotive Component Testing, Automotive Research and Design, Ballistics and Research, Design & Test.

The robust GX-5 Data Recording Processor (DRP) is available in either 4-channel or 8-channel versions while the choice of 3 different camera heads provides extreme versatility to handle a variety of requirements.

System Features:

- **Multi-Camera Heads:** NAC provides three (3) separate models providing a solution for specific size, light and resolution requirement.
- **Data Recording Processor (DRP):** Available in 4-channel and 8-channel versions, the GX-5 DRP includes a memory back-up function and IRIG time stamp recording. The DRP also provides for multi-camera synchronization and allows for both individual and multi-head image display on the LCD viewfinder.
- **Hi-G:** Ruggedized for onboard Hi-G applications, 100G's shock, 11ms.
- **Ultra High Light Sensitivity and High Resolution:** The choice of GX-5 camera heads allows the user to choose a model for specific size, light and resolution requirements!



Memrecam GX-5 DRP

The Memrecam GX-5 Data Recording Processor (DRP) is available in either a 4-channel or 8-channel version, depending on the application requirements. Different camera heads can be used with a single DRP to achieve specific viewing requirements. The DRP can be located up to 18 meters from the camera heads.

DRP Specifications:

Hi-G: 100G, 11ms

Size: 4ch DRP 270(W) x 146(H) x 150(D)mm
8ch DRP 290(W) x 142(H) x 240(D) mm

Memory: 2, 4, 8 GB (Memory segmentation is available)

Bit Density: 8 / 10 Bit

Functions include:

- Memory Optimization according to number of cameras
- Individual image display (live for setup and play back)
- Individual camera settings (except resolution, frame rate, bit density and trigger)
- Multi-head live view (for monitoring)



NAC Image Technology is a proud supplier of high-speed camera systems to the world's largest automotive manufacturers and Tier 1 suppliers. Join your colleagues in making the safe choice for reliable, high quality high-speed camera systems. Choose NAC and you'll see The Visible Difference!

Vertrieb:

MAK
BILDTECHNIK

MAK Bildtechnik GmbH
Hafenstr. 4
38442 Wolfsburg
Tel.: 05362 52423
Fax: 05362 52413
Email: info@MAK-Bildtechnik.de
www.MAK-Bildtechnik.de

GX-5 Camera Heads

A combination of camera heads can be used for specific application requirements. Synchronized recording among the GX-5 cameras allow for 3D measurement. Overlapping the field of views of the multi-heads provide for an extremely wide viewing area. Choose the camera heads suited for your particular requirements:

HR-Cam

(High resolution camera head) ISO 20,000 (mono)

Resolution (H x V)	Frame Rate (fps)
1280 x 960	100-1.000
1024 x 768	1.500
896 x 672	2.000
560 x 480	4.000
384 x 288	10.000

P-Cam and S-Cam

(Micro Camera Heads) ISO 4,000 (mono)

Resolution (H x V)	Frame Rate (fps)
640 x 480	100-1.000
512 x 384	1.500
448 x 336	2.000
320 x 240	4.000
192 x 144	10.000

The sensor on the S-Cam is separated from the camera head allowing the camera to reach even the smallest of spaces.